

Model	SkyPanel		L-Series			Caster Series	
							
Models	S30-C S60-C	S30-RP S60-RP	L5-C L5-TT L5-DT	L7-C L7-TT L7-DT	L10-C L10-TT L10-DT	BroadCaster 2 Plus	LoCaster 2 Plus
Dimensions	S30 models: 14 x 11.8 inches S60 models: 25.4 x 11.8 inches		15.5 x 10.9 x 11"	16.6 x 14.7 x 13.7"	22.9 x 19.3 x 22"	70 x 96 x 218 mm	
Luminous Output at 10 ft*	S30: 594 Lux S60: 1217 Lux	S30: 454 Lux S60: 1002 Lux	C: 368 Lux TT: 385 Lux DT: 477 Lux	C: 781 Lux TT: 886 Lux DT: 997 Lux	C: 1881 Lux TT: 2032 Lux DT: 2257 Lux	111 Lux	
Power Consumption	S30: 240 W S60: 450 W	S30: 240 W S60: 420 W	115 W	160 W – 220 W DT: 180 W – 220W	400 W – 510 W DT: 410 W - 510	35W nominal	
Dimming	0 - 100% Continuous		0 - 100% Continuous			0 - 100% Continuous	
Beam Angle	115° (Half Peak Angle)		14° - 50° (Half Peak Angle)			63° (Half Peak Angle)	
Color Range	2,800K – 10,000 K Green / magenta correction and RGBW color gamut control	3,200K or 5600K panel included**	C: 2,800 K - 10,000 K Green / magenta correction and RGBW color gamut control TT: 2,600K – 3,600K DT: 5,000 K - 6,500 K			2,800-6,500K Green / magenta correction and RGBW color gamut control	
Quality of Light	Soft LED Diffusion Panel	Remote Phosphor Panel	Focusable Fresnel			LED Array With a Prismatic Homogenizing Lens	
Control	On-Board Controller, 5-Pin DMX In and Through, Ether-Con LAN Network Connectivity, USB-A		5-Pin DMX In and Through, On-Board Controller, Mini-USB			4-Pin DMX In and Through	On-Board Controls
Mount	S30: Junior 1-1 / 8" Combo Pin S60: Spigot (Junior Pin)		Baby 5/8" / Junior 1-1 / 8" Combo Pin	28 mm Spigot (Junior Pin)		Thread 3/8"	

* 10.76 Lux = 1 Foot Candle. L-Series measurements in "Spot" mode
 ** 2,700 K; 3,200 K; 4,300 K; 5,600 K; 6,500 and 10,000 K available via interchangeable remote phosphor panels